

## 4MP Indoor Fixed-focal Wi-Fi Pan &

**Tilt Network Camera** 

DH-H4A



#### **Series Overview**

The Hero Series, which is under the Dahua Wireless series, are cameras that are not only easy to install and operate, but also perform outstandingly and are cost-effective. These highly sensitive cameras deliver crystal clear images and offer 360-degree monitoring without blind spots. Their powerful functions, such as human detection and auto tracking, not only assist with the accurate detection and continuous tracking of targets, but also reduce the occurrence of false alarms. It also features two-way talk, which allows you to freely communicate with your scene anytime, anywhere. Information is synchronously sent to your phone to keep you up-to-date. These cameras are widely used in small scenes such as shops and restaurants.



9:41			÷
<	Live	0	0-
¢¢	ð	å	66
t	71		4
	1/4	-	
D D	<]×	4	Do
Playback	0 C		(†) (*)
	^		
Alarm Messag	0	Ē	- v
• 07/05/2023			
<ul> <li>B<sup>P</sup> Human Detection</li> <li>1501-08</li> </ul>		10.5	
• ു Human D 1501.05	etection	10.5	
G Vehicle D     1501.05	etection	5	

## **Upgrade Your Experience with DMSS**

Dahua Mobile Security Surveillance (DMSS) is a professional remote surveillance management platform that offers remote monitoring, device migration, and sharing. When connected to the internet, the platform provides real-time alerts to improve surveillance efficiency and grant flexibility in security management.









## **Specifications**

#### Camera

Image Sensor

Max. Resolution Electronic Shutter Speed Illumination Distance Illuminator On/Off Control Illuminator Number Angle Adjustment Max. Aperture Field of View Video & Audio

Video Compression Video Frame Rate Resolution Video Bit Rate Day/Night WDR Motion Detection Image Rotation Built-in MIC Built-in Speaker Audio Compression 1/3" CMOS 2560 (H) × 1440 (V) Auto/Manual 1/3 s–1/100,000 s Up to 10 m (32.81 ft) (IR) Auto 1 (IR LED) Pan: 0° to 355°; Till:-5° to +80°

3.6 mm: F2.0

3.6 mm: H: 74°; V: 41°; D: 88°

H.265 Main stream: 2560 × 1440 @25 fps Sub stream: 640 × 480 @25 fps 4M (2560 × 1440); VGA (640 × 480) H.265: 80 kbps–4096 kbps Auto(ICR)/Color/B/W DWDR OFF/ON 0°/180° Yes, built-in Mic Yes, built-in speaker G.711a

#### Network

Network Port Wi-Fi Storage Management Software Mobile Client

#### General

Certifications CE 5 VDC, 1A Power Supply Basic: 1.8 W; Max. (video stream acquiring + IR + PTZ Rotation): Power Consumption 3.6 W -10 °C to +45 °C (+14 °F to +113 °F) Operating Temperature Operating Humidity ≤ 95% Casing Material Plastic Product Dimensions φ77.8 mm × 108.1 mm (φ3.06" × 4.26") Net Weight 204.2 g (0.45 lb)

RJ-45 (10/100 Base-T)

DMSS

iOS;Android

Micro SD card (up to 256 GB)

IEEE 802.11b/g/n 2.4–2.4835 GHz, 2.4 G

# What's in the box



### Tools:

Installation Position Map×1 Mounting Plate×1 Screw Package×1

#### Power:

Power Adapter×1

09127928902

Power Cable×1

QR Code×1 Quick Start Guide×1 Legal and regulation information×1

Documents:



#### Rev 002.000 © 2024