

3+3MP Outdoor Dual-Lens Pan & Tilt 4G Camera DH-P3D-3F-PV-4G



Series Overview

The Picoo Dual D1 4G Camera offers live surveillance from multiple angles with its fixed and PT lenses, enabling it to monitor two areas at the same time. As part of the Dahua Wireless family, this camera boasts exceptional capabilities. Both its lenses offer AI driven human and vehicle detection, significantly reducing the occurrence of false alarms. Additionally, the PT lens can identify moving targets and track them automatically. When the camera detects an intruder, it triggers sound and light alarms and sends notifications to the mobile client, keeping you up to date regardless of your location. Thanks to its 4G network capability, this camera delivers continuous surveillance even in Wi-Fi-limited environments, making it an ideal choice for remote outdoor locations such as farms, ranches, and orchards.





Upgrade Your Experience with DMSS

Dahua Mobile Security Surveillance (DMSS) is a professional remote surveillance management platform that offers remote monitoring, device migration, and sharing. When connected to the internet, the platform provides real-time alerts to improve surveillance efficiency and grant flexibility in security management.



09127928902







Video Bit Rate

Day/Night

Built-in MIC

Network

Storage

WDR

Specifications

Camera

Fixed Lens

Image Sensor Max. Resolution Illumination Distance Illuminator Number Focal Length Max. Aperture Field of View Pan/Tilt Range PT Lens Image Sensor

Max. Resolution Illumination Distance Illuminator Number Focal Length Max. Aperture Field of View

30 m (98.43 ft) (Warm light); 30 m (98.43 ft) (IR) 2 (IR); 2 (Warm light) 4 mm F1.6 H: 73.8°; V: 43.4°; D: 86.5° Pan: 0° to 290°; Tilt: -10° to +15° (Manual) 1/2.8" CMOS

1/2.8" CMOS

2304 (H) × 1296 (V)

2304 (H) × 1296 (V) 30 m (98.43 ft) (Warm light); 30 m (98.43 ft) (IR) 2 (IR); 2 (Warm light) 4 mm

F1.6 H: 73.8°; V: 43.4°; D: 86.5°

Pan: 0° to 350°; Tilt: 0° to +90° (Electric)

Smart Event

Pan/Tilt Range

Human Detection

Vehicle Detection

Audio and Video

Video Compression

Video Frame Rate

Smart H.265+;H.265;Smart H.264+;H.264B;H.264M;H.264H Main stream: 3M/1080p/720p/640 × 360@(1-15/15 fps) Sub stream 1: 640 × 360/QVGA@(1–15/15 fps)

Documents:

R.

Ũ

 \int

L

What's in the box

Tools:



Installation Position •• Map × 1 M Screw Package × 1

Waterproof Connector × 1

Yes

Yes

	QR Code × 1	Power Adapter × 1
1	Quick Start Guide × 1	
1	Legal and regulation information × 1	
1	Certification × 1	

Power:

09127928902



Warranty Card × 1 (-EUR model only)

Motion Detection Yes 180° Image Rotation Audio Compression PCM; G.711a; G.711Mu; G.726 Yes Built-in Speaker Yes EU LTE-FDD: B1/B3/B5/B7/B8/B20/B28 Wireless Carrier Frequency Band LA LTE-FDD: B2/B3/B4/B5/B7/B8/B28/B66 4G: Power class3: 23 dBm ±2 dB Max, Transmission Power Micro SD card (Supports max 256 GB) DMSS Management Software iOS; Android

H264: 80 kbps–2,048 kbps H265: 32kbps–1,536 kbps

Auto (ICR); Color/B/W

DWDR

Mobile Client General

Certifications	CE
Power Supply	12 VDC, 1 A ± 10%
Power Consumption	Basic: 5 W; Max: 12 W (illuminator + PTZ +sound and light warning)
Operating Temperature	-20 °C to +50 °C (-4 °F to +122 °F)
Operating Humidity	≤95%
Protection	IP66
Casing Material	Plastic
Product Dimensions	124.9 mm × 159.4 mm × 213.9 mm (4.92" × 6.28" × 8.42") (L × W × H)
Net Weight	610 g (1.34 lb)

19