

4MP Outdoor Wizcolor Fixed-focal 4G Pan & Tilt

Network Camera

DH-P4F-PV-4G

Series Overview

alhua Cooc

WizColor series cameras utilize groundbreaking technology to capture full-color images at night, overcoming the limitations of darkness. With advanced AI noise reduction and smart recognition, these cameras deliver images with rich colors and clear targets even in low light conditions, and eliminate motion blur in dynamic scenes. Whether in urban or rural settings, this series provides uninterrupted 24-hour high-definition intelligent monitoring for diverse environments.





Upgrade Your Experience with DMSS

Intuitive AIoT app for individual security

Accurate and timely



Remote Management Live view and recording history

Notifications and Alerts



Easy sharing

Safer device sharing with family and friends

Ê÷

High Security Stay secure with all data encrypted











Built-in MIC

Built-in Speaker

Network

Network Port

Interoperability

Mobile Client

Function

Certifications

Power Supply

Operating Humidity

Protection

Structure

Net Weight

Product Dimensions

Power

Storage

Specifications

Camera

Image Sensor

Max. Resolution

Electronic Shutter Speed

Min. Illumination

Illumination Distance

Illuminator Number

Lens

Focal Length Max. Aperture

Field of View

PTZ

Pan/Tilt Range

Smart Event

Human Detection

Vehicle Detection

Video

Video Compression

Video Frame Rate

Video Bit Rate

Day/Night

W/DR

Motion Detection Image Rotation

Audio

Audio Compression

1/1.8" CMOS 2560 (H) × 1440 (V) 1 s-1/30,000 s 0.0005 lux@F1.0 (Color, 30 IRE); 0 lux (illuminator on) 30 m (164.04 ft) (Warm light) 4 (warm light)

4 mm F1.0 H: 97°; V: 52°; D: 114°

Yes

Pan: 0° to 345°; Tilt: 0° to +90°

Yes

Smart H.265+; H.264M; H.264H; Smart H.264+; H.265; H.264B; MJPEG Main stream: 4M/1080p/720p@(1–25/30 fps) Sub stream 1: D1/VGA/CIF@(1–25/30 fps)

H264: 3,072 kbps–15,104 kbps H265: 1,280 kbps–9,216 kbps Color/B/W

DWDR Yes 180°

PCM, G.711A, G.711Mu

What's in the box

Tools: Installation Position .. Map × 1

x 1

M Screw Package × 1 Mounting Plate × 1 2 Waterproof Connector

QR Code × 1 Quick Start Guide × 1 Legal and regulation information × 1 Certification × 1 Π Wireless Frequency



Warranty Card × 1 (Only for-EUR)

EAU LTE-FDD: B1/B3/B5/B7/B8/B20/B28 TDD:B38/40/41 EUR LTE-FDD: B1/B3/B5/B7/B8/B20/B28 Wireless Carrier Frequency Band TDD:B38/40/41 LA LTE-FDD: B2/B3/B4/B5/B7/B8/B28/B66 Max. Transmission Power 4G: Power class3: 23dBm±2dB ONVIF (Profile S & Profile G & Profile T); SDK; CGI Micro SD card (Up to 2<mark>56 GB); FT</mark>P DSS Pro; 5 Series NVR; DMSS Management Software Android; iOS Abnormal Sound Alarm Yes Certification CE 12 VDC,1 A ± 10% (included) Power Consumption Basic: 3 W Max: 7.5 W (illuminator + PTZ) Environment Operating Temperature -30 °C to +55 °C (-22 °F to +131 °F)

RJ-45 (10/100 Base-T)

Yes

Yes

≤95%

TVS 2000 V lightning proof; Waterproof and Dustproof; surge protection; voltage transient protection

153.5 mm × Φ129.3 mm (6.04" × Φ5.09") 0.66 kg (1.46 lb)

09127928902





Documents: L

e 🖸 Power Adapter × 1







